

The power and performance you need

High performance 1/5 horsepower pump delivers 0 - 26 inHg (0 - 660 mmHg) — among the highest in the industry

- **Protected:** Dual protection system with a float shut-off in the canister lid and an Inline Hydrophobic Filter to prevent back flow of fluid as well as airborne contaminants from entering the pump.
- **High durability:** Features a protective canister bracket that holds the canister and protects the gauge and adjustment knob from accidents.
- **Convenient:** Features a Velco™ strap that allows you to wrap the power cord for improved portability. Extra strength premium suction feet safely and securely attach the unit to most surfaces, preventing spillage.
- **Safe:** Automatic resetting thermal limit switch prevents the unit from overheating.



Specifications

Dimensions:

- Length: 13.25" (33.7 cm)
- Width: 8" (20.3 cm)
- Height: 9.75" (24.8 cm)

Weight: 12.6 lbs. (5.7 kg)**Shipping Weight:**

14.5 lbs. (6.6 kg)

Motor:

120 VAC, 60 Hz, 5 Amps

Vacuum Range: 0 - 26 inHg**Horsepower:** 1/5**Operating Temp. Range:**

50° F to 104° F (10° C to 40° C)

Storage Conditions

- Temp.: -4° F to 104° (-20° to 40° C)
- Humidity: Max 95% non-condensing